



TECHNICAL DATA		50 Hz	60 Hz
• Power	kW - HP	1,5 - 2,01	1,75 - 2,35
• Input voltages ^{1) 2)} Current settings available	V A	115 D 22,0 D 230 Y 11,0 Y	115 D 24,0 D 230 Y 12,0 Y
• Electrical cable length Electrical plug		6 meters Not supplied	
• ATEX mark		 II 3D - Ex c t IIIB T135°C Dc	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmHg	2.600 1.900	3.100 1.800
• Maximum air flow	l/min - m³/h	3.500 - 210	4.167 - 250
• Acoustic level ^{d)}	dB (A)	64	70
• Dust Bin: capacity	l	25	
• Diameters: material inlet	mm	50	
• Dimensions: L x W (W.090) x H Weight	mm kg	830 x 460 (460) x 830 29	
• Packing size ⁵⁾ : L x W (W.090) x H Weight	mm kg	871 x 671 (671) x 1.000 34	
• Primary filter		Star filter	
Surface area Diameter	cm² - m² mm	7.000 - 0,7 360	
Dust Class ^{6) e)} Media ⁷⁾		M Antistatic polyester	
Filter cleaning ⁸⁾		Ergonomic manual shaker	
• Automatic filter cleaning - Optional		---	
Surface area Nominal output	cm² - m² m³/h	---	
Dust Class ^{e)} Media		---	
Compressed air consumption pressure	nl/min bar	---	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm² - m² m³/h	17.000 - 1,7 ---	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	



¹⁾ Other input voltages upon request

²⁾ **Default factory setting: 230 V**

³⁾ Maximum vacuum in continuous run

⁴⁾ ---

⁵⁾ Standard packing size

⁶⁾ PTFE coated antistatic star filter available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ ---

⁹⁾ AISI 316L cleaned welding and inner mirror polished

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• **KH1636.100.022B** 25 litres single phase vacuum dust collector - IP55 - ATEX zone 22

OPTIONS

• 001	AISI 304 stainless steel dust bin	
•	AISI 316L stainless steel dust bin, "pharma finishing" ⁹⁾	
• 003	AISI 304 stainless steel completely made	
•	AISI 316L stainless steel completely made, "pharma finishing" ⁹⁾	
• 005	Upstream absolute filter (HEPA)	
•	Overheating safety relief valve	
•	Silencer for painted version	included
•	Silencer for stainless steel version (.003)	included
• 090	On/off switch with thermal protection	
• 100	Fitted with single-phase vacuum unit	included

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.

Versions available: **L-M-H** filtration (for hazardous powders vacuuming) certification