

TECHNICAL DATA			50 Hz	60 Hz
• Power		kW - HP	7,5 - 10	not available
• Input voltages ^{1) 2)} Current		settings available V A	---	not available
			345D ... 415D 15,1D	not available
• Electrical cable length Electrical plug type			9 meters 4 poles (5 poles upon request)	
• ATEX mark			NO ATEX	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}			IP55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾		mmH ₂ O	4.200 2.500	not available
• Maximum air flow		l/min - m ³ /h	13.500 - 810	not available
• Acoustic level ^{d)}		dB (A)	78	not available
• Dust bin:	capacity wheels diameter	l mm	90 60	
• Diameters:	material inlet wheels ⁴⁾ (front - rear)	mm	100 200 - 150	
• Dimensions:	L x W x H (H.005 - H.008) Weight	mm kg	1.285 x 650 x 1.772 (1.982 - 2.072) 200	
• Packing size ⁵⁾ :	L x W x H (H.005 - H.008) Weight	mm kg	1.500 x 800 x 2.000 (2.100 - 2.190) 220	
• Primary filter			Star filter	
Surface area Diameter		cm ² - m ² mm	35.000 - 3,5 560	
Dust Class ^{6) e)} Media ⁷⁾			L Polyester	
Filter cleaning ⁸⁾			Ergonomic manual shaker	
• Automatic filter cleaning - Optional			Cartridges kit	
Surface area Nominal output		cm ² - m ² m ³ /h	94.800 - 9,48 3.410	
Dust Class ^{e)} Media			M Antistatic polyester	
Compressed air consumption pressure		nl/min bar	48 4 ÷ 6	
• Upstream absolute filter - Optional			HEPA 14	
Surface area Nominal output		cm ² - m ² m ³ /h	120.000 - 12 1.200	
Dust Class ^{f)} Media			H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)			99,995%	

¹⁾ Other input voltages upon request

²⁾ Default factory setting: 400 V - 50 Hz

³⁾ Maximum vacuum in continuous run

⁴⁾ Marks proof wheels with bearings not suitable

⁵⁾ Standard packing size

⁶⁾ M class filters available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ Electric filter shaker with push-button as option (006)

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS	
• KB7P	90 litres three phase vacuum cleaner

OPTIONS	
• 001	AISI 304 stainless steel dust bin (instead of the painted one)
• 002	AISI 304 stainless steel dust bin and filtering chamber
• 003	AISI 304 stainless steel completely made
• 004	Liquids switch off
• 005	Upstream absolute filter (HEPA) with M dust class primary filter - version: painted stainless steel
• 006	Electric filter shaker with push-button
• 008	Automatic reverse jet cartridge filtering system
• 075	Dust bin overfilling switch off
•	Reinforced dust bin
•	On/off arrangement through micro-switch(es)
•	Overheating safety relief valve
•	Disposal bag balance

For an effective and proper use according to your application requirements, please see our AP catalogue.

Versions available: • L-M-H filtration (for hazardous powders vacuuming) certification
• ATEX certified machines

