

TECHNICAL DATA

• Power		kW - HP	8,7 - 11,8
• Fuel			Gasoline
• ATEX mark			NO ATEX
• Maximum vacuum Optimum vacuum ¹⁾		mm H ₂ O	3.300 - 2.500
• Maximum air flow		l/min - m ³ /h	9.000 - 540
• Acoustic level ^{a)}		dB (A)	98
• Dust bin:	capacity		90
	wheels diameter	mm	60
• Diameters:	material inlet	mm	70
	wheels ²⁾ (front - rear)		200 150
• Dimensions:	L x W x H Weight	mm kg	1.320 x 700 x 1.620 166
• Packing size ³⁾ :	L x W x H Weight	mm kg	1.500 x 800 x 1.750 181
• Primary filter			Star filter
Surface area Diameter		cm ² - m ² mm	35.000 - 3,5 560
Dust Class ^{b)} Media ⁴⁾			M PE/PU
Filter cleaning			Ergonomic manual shaker
• Upstream absolute filter - Optional			HEPA 14
Surface area Nominal output		cm ² - m ² m ³ /h	105.000 - 10,5 ---
Dust Class ^{c)} Media			H14 Glass fibre
Efficiency M.P.P.S. ^{c)} (with 0,18 µm particles)			99,995%

¹⁾ Maximum vacuum in continuous run

²⁾ Marks proof wheels with bearings

³⁾ Standard packing size

⁴⁾ Other materials available according to the material to be vacuumed



Normatives: a) EN60704-2-1; b) EN60335-2-69; c) EN1822

AVAILABLE VERSIONS

• KT856P	90 litres dust bin gasoline fuel vacuum cleaner

OPTIONS

• 001	AISI 304 stainless steel dust bin (instead of the painted one)	
• 002	AISI 304 stainless steel dust bin and filtering chamber	
• 003	AISI 304 stainless steel completely made	upon request
• 004	Mechanical liquids switch off	upon request
• 005	Upstream absolute filter (HEPA)	

For an effective and proper use according to your application requirements, please see our AP catalogue.

Versions available: • L-M-H filtration (for hazardous powders vacuuming) certification