

TECHNICAL DATA

• Power		kW - HP	8,7 - 11,8
• Fuel			Gasoline
• ATEX mark			NO ATEX
• Maximum vacuum Optimum vacuum ¹⁾		mm H ₂ O	3.300 - 2.500
• Maximum air flow		l/min - m ³ /h	9.000 - 540
• Acoustic level ^{a)}		dB (A)	98
• Diameters:	material inlet		70
	wheels ²⁾ (front - rear)	mm	200 150
• Dimensions:	L x W x H (down) Weight	mm kg	1.320 x 700 x 1.750 (1.620) 166
• Packing size ³⁾ :	L x W x H (down) Weight	mm kg	1.500 x 800 x 1.880 (1.730) 181
• Primary filter			Star filter
Surface area Diameter			35.000 - 3,5 560
Dust Class ^{b)} Media ⁴⁾			M PE/PU
Filter cleaning		cm ² - m ² mm	Ergonomic manual shaker
• Upstream absolute filter - Optional			HEPA 14
Surface area Nominal output			105.000 - 10,5 ---
Dust Class ^{c)} Media			H14 Glass fibre
Efficiency M.P.P.S. ^{c)} (with 0,18 µm particles)		cm ² - m ² m ³ /h	99,995%
• Dust collection system			LONGOPAC
Bag length (4 units)		m	20
Material			3-layer coextruded polyethylene (PE)
Thickness		µm	68

¹⁾ Maximum vacuum in continuous run

²⁾ Marks proof wheels with bearings

³⁾ Standard packing size

⁴⁾ Other materials available according to the material to be vacuumed



Normatives: a) EN60704-2-1; b) EN60335-2-69; c) EN1822

AVAILABLE VERSIONS

• **KT856P.084** Longopac collection system gasoline fuel vacuum cleaner

OPTIONS

• 002	AISI 304 stainless steel filtering chamber	upon request
• 003	AISI 304 stainless steel completely made	upon request
• 005	Upstream absolute filter (HEPA)	upon request

For an effective and proper use according to your application requirements, please see our AP catalogue.

Versions available: • **L-M-H** filtration (for hazardous powders vacuuming) certification